



## Fast IGBT in NPT-technology with soft, fast recovery anti-parallel EmCon diode

- 75% lower  $E_{off}$  compared to previous generation combined with low conduction losses
- Short circuit withstand time – 10  $\mu$ s
- Designed for:
  - Motor controls
  - Inverter
- NPT-Technology for 600V applications offers:
  - very tight parameter distribution
  - high ruggedness, temperature stable behaviour
  - parallel switching capability
- Very soft, fast recovery anti-parallel EmCon diode
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC<sup>1</sup> for target applications
- Complete product spectrum and PSpice Models : <http://www.infineon.com/igbt/>



| Type      | $V_{CE}$ | $I_C$ | $V_{CE(sat)}$ | $T_j$ | Marking | Package       |
|-----------|----------|-------|---------------|-------|---------|---------------|
| SKP10N60A | 600V     | 10A   | 2.3V          | 150°C | K10N60  | PG-TO-220-3-1 |
| SKW10N60A | 600V     | 10A   | 2.3V          | 150°C | K10N60  | PG-TO-247-3   |

### Maximum Ratings

| Parameter  | Symbol         | Value      | Unit             |
|--|----------------|------------|------------------|
| Collector-emitter voltage  | $V_{CE}$       | 600        | V                |
| DC collector current   | $I_C$          | 20         | A                |
| $T_C = 25^\circ\text{C}$   |                | 20         |                  |
| $T_C = 100^\circ\text{C}$  |                | 10.6       |                  |
| Pulsed collector current, $t_p$ limited by $T_{jmax}$                      | $I_{Cpuls}$    | 40         |                  |
| Turn off safe operating area   | -              | 40         |                  |
| $V_{CE} \leq 600\text{V}, T_j \leq 150^\circ\text{C}$                      |                |            |                  |
| Diode forward current  | $I_F$          | 21         |                  |
| $T_C = 25^\circ\text{C}$   |                | 21         |                  |
| $T_C = 100^\circ\text{C}$  |                | 10         |                  |
| Diode pulsed current, $t_p$ limited by $T_{jmax}$                          | $I_{Fpuls}$    | 42         |                  |
| Gate-emitter voltage   | $V_{GE}$       | $\pm 20$   | V                |
| Short circuit withstand time <sup>2</sup>                                  | $t_{SC}$       | 10         | $\mu$ s          |
| $V_{GE} = 15\text{V}, V_{CC} \leq 600\text{V}, T_j \leq 150^\circ\text{C}$ |                |            |                  |
| Power dissipation  | $P_{tot}$      | 92         | W                |
| $T_C = 25^\circ\text{C}$   |                |            |                  |
| Operating junction and storage temperature                                 | $T_j, T_{stg}$ | -55...+150 | $^\circ\text{C}$ |
| Soldering temperature  | $T_s$          | 260        | $^\circ\text{C}$ |
| wavesoldering, 1.6 mm (0.063 in.) from case for 10s                        |                |            |                  |

<sup>1</sup> J-STD-020 and JESD-022

<sup>2</sup> Allowed number of short circuits: <1000; time between short circuits: >1s.

### Thermal Resistance

| Parameter                                 | Symbol      | Conditions                      | Max. Value | Unit |
|---|-------------|---------------------------------|------------|------|
| <b>Characteristic</b>                     |             |                                 |            |      |
| IGBT thermal resistance, junction – case  | $R_{thJC}$  |                                 | 1.35       | K/W  |
| Diode thermal resistance, junction – case | $R_{thJCD}$ |                                 | 2.4        |      |
| Thermal resistance, junction – ambient    | $R_{thJA}$  | PG-TO-220-3-1<br>PG-TO-247-3-21 | 62<br>40   |      |

### Electrical Characteristic, at $T_j = 25^\circ\text{C}$ , unless otherwise specified

| Parameter   | Symbol        | Conditions  | Value    |             |             | Unit    |
|---|---------------|---|----------|-------------|-------------|---------|
|   |               |   | min.     | Typ.        | max.        |         |
| <b>Static Characteristic</b>                                      |               |   |          |             |             |         |
| Collector-emitter breakdown voltage                               | $V_{(BR)CES}$ | $V_{GE}=0V, I_C=500\mu A$   | 600      | -           | -           | V       |
| Collector-emitter saturation voltage                              | $V_{CE(sat)}$ | $V_{GE} = 15V, I_C=10A$<br>$T_j=25^\circ\text{C}$<br>$T_j=150^\circ\text{C}$          | 1.7<br>- | 2<br>2.3    | 2.4<br>2.8  |         |
| Diode forward voltage   | $V_F$         | $V_{GE}=0V, I_F=10A$<br>$T_j=25^\circ\text{C}$<br>$T_j=150^\circ\text{C}$             | 1.2<br>- | 1.4<br>1.25 | 1.8<br>1.65 |         |
| Gate-emitter threshold voltage                                    | $V_{GE(th)}$  | $I_C=300\mu A, V_{CE}=V_{GE}$   | 3        | 4           | 5           |         |
| Zero gate voltage collector current                               | $I_{CES}$     | $V_{CE}=600V, V_{GE}=0V$<br>$T_j=25^\circ\text{C}$<br>$T_j=150^\circ\text{C}$         | -<br>-   | -<br>-      | 40<br>1500  | $\mu A$ |
| Gate-emitter leakage current                                      | $I_{GES}$     | $V_{CE}=0V, V_{GE}=20V$   | -        | -           | 100         | nA      |
| Transconductance  | $g_{fs}$      | $V_{CE}=20V, I_C=10A$   | -        | 6.7         | -           | S       |
| <b>Dynamic Characteristic</b>                                     |               |   |          |             |             |         |
| Input capacitance   | $C_{iss}$     | $V_{CE}=25V,$   | -        | 550         | 660         | pF      |
| Output capacitance  | $C_{oss}$     | $V_{GE}=0V,$  | -        | 62          | 75          |         |
| Reverse transfer capacitance                                      | $C_{riss}$    | $f=1\text{MHz}$   | -        | 42          | 51          |         |
| Gate charge   | $Q_{Gate}$    | $V_{CC}=480V, I_C=10A$<br>$V_{GE}=15V$  | -        | 52          | 68          | nC      |
| Internal emitter inductance<br>measured 5mm (0.197 in.) from case | $L_E$         | PG-TO-220-3-1   | -        | 7           | -           | nH      |
|   |               | PG-TO-247-3-21  | -        | 13          | -           |         |
| Short circuit collector current <sup>2)</sup>                     | $I_{C(SC)}$   | $V_{GE}=15V, t_{SC}\leq 10\mu s$<br>$V_{CC}\leq 600V,$<br>$T_j\leq 150^\circ\text{C}$ | -        | 100         | -           | A       |

<sup>2)</sup> Allowed number of short circuits: <1000; time between short circuits: >1s.


### Switching Characteristic, Inductive Load, at $T_j=25\text{ }^\circ\text{C}$

| Parameter  | Symbol       | Conditions  | Value |       |                        | Unit |
|--|--------------|---|-------|-------|------------------------|------|
|  |              |   | min.  | typ.  | max.                   |      |
| <b>IGBT Characteristic</b>                                       |              |   |       |       |                        |      |
| Turn-on delay time   | $t_{d(on)}$  | $T_j=25\text{ }^\circ\text{C}$ ,<br>$V_{CC}=400\text{V}$ , $I_C=10\text{A}$ ,<br>$V_{GE}=0/15\text{V}$ ,<br>$R_G=25\Omega$ ,<br>$L_{\sigma}^{(1)}=180\text{nH}$ ,<br>$C_{\sigma}^{(1)}=55\text{pF}$<br>Energy losses include<br>"tail" and diode<br>reverse recovery. | -     | 28    | 34                     | ns   |
| Rise time  | $t_r$        |   | -     | 12    | 15                     |      |
| Turn-off delay time  | $t_{d(off)}$ |   | -     | 178   | 214                    |      |
| Fall time  | $t_f$        |   | -     | 24    | 29                     |      |
| Turn-on energy   | $E_{on}$     |   | -     | 0.15  | 0.173                  | mJ   |
| Turn-off energy  | $E_{off}$    |   | -     | 0.17  | 0.221                  |      |
| Total switching energy   | $E_{ts}$     |   | -     | 0.320 | 0.394                  |      |
| <b>Anti-Parallel Diode Characteristic</b>                        |              |   |       |       |                        |      |
| Diode reverse recovery time                                      | $t_{rr}$     | $T_j=25\text{ }^\circ\text{C}$ ,<br>$V_R=200\text{V}$ , $I_F=10\text{A}$ ,<br>$di_F/dt=200\text{A}/\mu\text{s}$   | -     | 220   | -                      | ns   |
|  | $t_S$        |   | -     | 20    | -                      |      |
|  | $t_F$        |   | -     | 200   | -                      |      |
| Diode reverse recovery charge                                    | $Q_{rr}$     |   | -     | 310   | -                      | nC   |
| Diode peak reverse recovery current                              | $I_{rrm}$    |   | -     | 4.5   | -                      | A    |
| Diode peak rate of fall of reverse recovery current during $t_b$ | $di_{rr}/dt$ | -   | 180   | -     | $\text{A}/\mu\text{s}$ |      |

### Switching Characteristic, Inductive Load, at $T_j=150\text{ }^\circ\text{C}$

| Parameter  | Symbol       | Conditions   | Value |       |                        | Unit |
|--|--------------|--|-------|-------|------------------------|------|
|  |              |  | min.  | typ.  | max.                   |      |
| <b>IGBT Characteristic</b>                                       |              |  |       |       |                        |      |
| Turn-on delay time   | $t_{d(on)}$  | $T_j=150\text{ }^\circ\text{C}$<br>$V_{CC}=400\text{V}$ , $I_C=10\text{A}$ ,<br>$V_{GE}=0/15\text{V}$ ,<br>$R_G=25\Omega$<br>$L_{\sigma}^{(1)}=180\text{nH}$ ,<br>$C_{\sigma}^{(1)}=55\text{pF}$<br>Energy losses include<br>"tail" and diode<br>reverse recovery. | -     | 28    | 34                     | ns   |
| Rise time  | $t_r$        |  | -     | 12    | 15                     |      |
| Turn-off delay time  | $t_{d(off)}$ |  | -     | 198   | 238                    |      |
| Fall time  | $t_f$        |  | -     | 26    | 32                     |      |
| Turn-on energy   | $E_{on}$     |  | -     | 0.260 | 0.299                  | mJ   |
| Turn-off energy  | $E_{off}$    |  | -     | 0.280 | 0.364                  |      |
| Total switching energy   | $E_{ts}$     |  | -     | 0.540 | 0.663                  |      |
| <b>Anti-Parallel Diode Characteristic</b>                        |              |  |       |       |                        |      |
| Diode reverse recovery time                                      | $t_{rr}$     | $T_j=150\text{ }^\circ\text{C}$<br>$V_R=200\text{V}$ , $I_F=10\text{A}$ ,<br>$di_F/dt=200\text{A}/\mu\text{s}$   | -     | 350   | -                      | ns   |
|  | $t_S$        |  | -     | 36    | -                      |      |
|  | $t_F$        |  | -     | 314   | -                      |      |
| Diode reverse recovery charge                                    | $Q_{rr}$     |  | -     | 690   | -                      | nC   |
| Diode peak reverse recovery current                              | $I_{rrm}$    |  | -     | 6.3   | -                      | A    |
| Diode peak rate of fall of reverse recovery current during $t_b$ | $di_{rr}/dt$ | -  | 200   | -     | $\text{A}/\mu\text{s}$ |      |


<sup>1)</sup> Leakage inductance  $L_{\sigma}$  and Stray capacity  $C_{\sigma}$  due to dynamic test circuit in Figure E.



$f$ , SWITCHING FREQUENCY

**Figure 1. Collector current as a function of switching frequency**


( $T_j \leq 150^\circ\text{C}$ ,  $D = 0.5$ ,  $V_{CE} = 400\text{V}$ ,  
 $V_{GE} = 0/+15\text{V}$ ,  $R_G = 25\Omega$ )



$V_{CE}$ , COLLECTOR-EMITTER VOLTAGE

**Figure 2. Safe operating area**


( $D = 0$ ,  $T_C = 25^\circ\text{C}$ ,  $T_j \leq 150^\circ\text{C}$ )



$T_C$ , CASE TEMPERATURE

**Figure 3. Power dissipation as a function of case temperature**


( $T_j \leq 150^\circ\text{C}$ )




$T_C$ , CASE TEMPERATURE

**Figure 4. Collector current as a function of case temperature**


( $V_{GE} \leq 15\text{V}$ ,  $T_j \leq 150^\circ\text{C}$ )




**Figure 5. Typical output characteristics**  
( $T_j = 25^\circ\text{C}$ )




**Figure 6. Typical output characteristics**  
( $T_j = 150^\circ\text{C}$ )



**Figure 7. Typical transfer characteristics**  
( $V_{CE} = 10\text{V}$ )




**Figure 8. Typical collector-emitter saturation voltage as a function of junction temperature**  
( $V_{GE} = 15\text{V}$ )



$I_C$ , COLLECTOR CURRENT

**Figure 9. Typical switching times as a function of collector current**


(inductive load,  $T_j = 150^\circ\text{C}$ ,  $V_{CE} = 400\text{V}$ ,  $V_{GE} = 0/+15\text{V}$ ,  $R_G = 25\Omega$ , Dynamic test circuit in Figure E)



$R_G$ , GATE RESISTOR

**Figure 10. Typical switching times as a function of gate resistor**


(inductive load,  $T_j = 150^\circ\text{C}$ ,  $V_{CE} = 400\text{V}$ ,  $V_{GE} = 0/+15\text{V}$ ,  $I_C = 10\text{A}$ , Dynamic test circuit in Figure E)



$T_j$ , JUNCTION TEMPERATURE

**Figure 11. Typical switching times as a function of junction temperature**


(inductive load,  $V_{CE} = 400\text{V}$ ,  $V_{GE} = 0/+15\text{V}$ ,  $I_C = 10\text{A}$ ,  $R_G = 25\Omega$ , Dynamic test circuit in Figure E)



$T_j$ , JUNCTION TEMPERATURE


**Figure 12. Gate-emitter threshold voltage as a function of junction temperature**

( $I_C = 0.3\text{mA}$ )




$I_C$ , COLLECTOR CURRENT

**Figure 13. Typical switching energy losses as a function of collector current**  
(inductive load,  $T_j = 150^\circ\text{C}$ ,  $V_{CE} = 400\text{V}$ ,  $V_{GE} = 0/+15\text{V}$ ,  $R_G = 25\Omega$ ,  
Dynamic test circuit in Figure E)




$R_G$ , GATE RESISTOR

**Figure 14. Typical switching energy losses as a function of gate resistor**  
(inductive load,  $T_j = 150^\circ\text{C}$ ,  $V_{CE} = 400\text{V}$ ,  $V_{GE} = 0/+15\text{V}$ ,  $I_C = 10\text{A}$ ,  
Dynamic test circuit in Figure E)




$T_j$ , JUNCTION TEMPERATURE

**Figure 15. Typical switching energy losses as a function of junction temperature**  
(inductive load,  $V_{CE} = 400\text{V}$ ,  $V_{GE} = 0/+15\text{V}$ ,  $I_C = 10\text{A}$ ,  $R_G = 25\Omega$ ,  
Dynamic test circuit in Figure E)




$t_p$ , PULSE WIDTH


**Figure 16. IGBT transient thermal impedance as a function of pulse width**  
( $D = t_p / T$ )




$Q_{GE}$ , GATE CHARGE  
**Figure 17. Typical gate charge**  
( $I_C = 10A$ )



$V_{CE}$ , COLLECTOR-EMITTER VOLTAGE  
**Figure 18. Typical capacitance as a function of collector-emitter voltage**  
( $V_{GE} = 0V, f = 1MHz$ )




**Figure 19. Short circuit withstand time as a function of gate-emitter voltage**  
( $V_{CE} = 600V, \text{start at } T_j = 25^\circ C$ )




**Figure 20. Typical short circuit collector current as a function of gate-emitter voltage**  
( $V_{CE} \leq 600V, T_j = 150^\circ C$ )







$di_F/dt$ , DIODE CURRENT SLOPE  
**Figure 21. Typical reverse recovery time as a function of diode current slope**  
 ( $V_R = 200V$ ,  $T_j = 125^\circ C$ ,  
 Dynamic test circuit in Figure E)




$di_F/dt$ , DIODE CURRENT SLOPE  
**Figure 22. Typical reverse recovery charge as a function of diode current slope**  
 ( $V_R = 200V$ ,  $T_j = 125^\circ C$ ,  
 Dynamic test circuit in Figure E)




$di_F/dt$ , DIODE CURRENT SLOPE  
**Figure 23. Typical reverse recovery current as a function of diode current slope**  
 ( $V_R = 200V$ ,  $T_j = 125^\circ C$ ,  
 Dynamic test circuit in Figure E)




$di_F/dt$ , DIODE CURRENT SLOPE  
**Figure 24. Typical diode peak rate of fall of reverse recovery current as a function of diode current slope**  
 ( $V_R = 200V$ ,  $T_j = 125^\circ C$ ,  
 Dynamic test circuit in Figure E)



**Figure 25. Typical diode forward current as a function of forward voltage**




**Figure 26. Typical diode forward voltage as a function of junction temperature**



**Figure 27. Diode transient thermal impedance as a function of pulse width ( $D = t_p / T$ )**

PG-TO220-3-1



| DIM      | MILLIMETERS |       | INCHES |       |
|----------|-------------|-------|--------|-------|
|          | MIN         | MAX   | MIN    | MAX   |
| A        | 4.30        | 4.57  | 0.169  | 0.180 |
| A1       | 1.17        | 1.40  | 0.046  | 0.055 |
| A2       | 2.15        | 2.72  | 0.085  | 0.107 |
| b        | 0.65        | 0.86  | 0.026  | 0.034 |
| b1       | 0.95        | 1.40  | 0.037  | 0.055 |
| b2       | 0.95        | 1.15  | 0.037  | 0.045 |
| b3       | 0.65        | 1.15  | 0.026  | 0.045 |
| c        | 0.33        | 0.60  | 0.013  | 0.024 |
| D        | 14.81       | 15.95 | 0.583  | 0.628 |
| D1       | 8.51        | 9.45  | 0.335  | 0.372 |
| D2       | 12.19       | 13.10 | 0.480  | 0.516 |
| E        | 9.70        | 10.36 | 0.382  | 0.408 |
| E1       | 6.50        | 8.60  | 0.256  | 0.339 |
| e        | 2.54        |       | 0.100  |       |
| e1       | 5.08        |       | 0.200  |       |
| N        | 3           |       | 3      |       |
| H1       | 5.90        | 6.90  | 0.232  | 0.272 |
| L        | 13.00       | 14.00 | 0.512  | 0.551 |
| L1       | -           | 4.80  | -      | 0.189 |
| $\phi P$ | 3.60        | 3.89  | 0.142  | 0.153 |
| Q        | 2.60        | 3.00  | 0.102  | 0.118 |

DOCUMENT NO.  
Z8B00003318



SCALE

EUROPEAN PROJECTION

ISSUE DATE  
23-08-2007

REVISION  
05

PG-TO247-3



| DIM | MILLIMETERS |       | INCHES |       |
|-----|-------------|-------|--------|-------|
|     | MIN         | MAX   | MIN    | MAX   |
| A   | 4.90        | 5.16  | 0.193  | 0.203 |
| A1  | 2.27        | 2.53  | 0.089  | 0.099 |
| A2  | 1.85        | 2.11  | 0.073  | 0.083 |
| b   | 1.07        | 1.33  | 0.042  | 0.052 |
| b1  | 1.90        | 2.41  | 0.075  | 0.095 |
| b2  | 1.90        | 2.16  | 0.075  | 0.085 |
| b3  | 2.87        | 3.38  | 0.113  | 0.133 |
| b4  | 2.87        | 3.13  | 0.113  | 0.123 |
| c   | 0.55        | 0.68  | 0.022  | 0.027 |
| D   | 20.82       | 21.10 | 0.820  | 0.831 |
| D1  | 16.25       | 17.65 | 0.640  | 0.695 |
| D2  | 1.05        | 1.35  | 0.041  | 0.053 |
| E   | 15.70       | 16.03 | 0.618  | 0.631 |
| E1  | 13.10       | 14.15 | 0.516  | 0.557 |
| E2  | 3.68        | 5.10  | 0.145  | 0.201 |
| E3  | 1.68        | 2.60  | 0.066  | 0.102 |
| e   | 5.44        |       | 0.214  |       |
| N   | 3           |       | 3      |       |
| L   | 19.80       | 20.31 | 0.780  | 0.799 |
| L1  | 4.17        | 4.47  | 0.164  | 0.176 |
| øP  | 3.50        | 3.70  | 0.138  | 0.146 |
| Q   | 5.49        | 6.00  | 0.216  | 0.236 |
| S   | 6.04        | 6.30  | 0.238  | 0.248 |

DOCUMENT NO.  
Z8B00003327

SCALE

EUROPEAN PROJECTION

ISSUE DATE  
17-12-2007

REVISION  
03




Figure A. Definition of switching times




Figure C. Definition of diodes switching characteristics




Figure D. Thermal equivalent circuit




Figure B. Definition of switching losses




Figure E. Dynamic test circuit  
Leakage inductance  $L_{\sigma} = 180\text{nH}$   
and Stray capacity  $C_{\sigma} = 55\text{pF}$ .

**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2008 Infineon Technologies AG**  
**All Rights Reserved.**

### **Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

### **Information**

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

### **Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.