

IGBT Module

SK20MLI066

Target Data

Features


- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- Trench IGBT technology
- CAL technology FWD

Typical Applications*

- 3 Level Inverter
- UPS

Remarks

- Visol = 3000V AC, 1s, 50Hz
- Dynamic measure: DUT= IGBT (Gate pin 1) and Neutral Clamp Diode (Kathode pin 16) as free-wheeling diode



MLI


Absolute Maximum Ratings		$T_s = 25\text{ }^\circ\text{C}$, unless otherwise specified	
Symbol	Conditions	Values	Units
IGBT			
V_{CES}	$T_j = 25\text{ }^\circ\text{C}$	600	V
I_C	$T_j = 175\text{ }^\circ\text{C}$	$T_s = 25\text{ }^\circ\text{C}$	30 A
		$T_s = 70\text{ }^\circ\text{C}$	24 A
I_{CRM}	$I_{CRM} = 2 \times I_{Cnom}$	40	A
V_{GES}		± 20	V
t_{psc}	$V_{CC} = 360\text{ V}$; $V_{GE} \leq 20\text{ V}$; $T_j = 150\text{ }^\circ\text{C}$ $V_{CES} < 600\text{ V}$	6	μs

Inverse Diode			
I_F	$T_j = 175\text{ }^\circ\text{C}$	$T_s = 25\text{ }^\circ\text{C}$	30 A
		$T_s = 70\text{ }^\circ\text{C}$	24 A
I_{FRM}	$I_{FRM} = 2 \times I_{Fnom}$	40	A
I_{FSM}	$t_p = 10\text{ ms}$; half sine wave $T_j = 150\text{ }^\circ\text{C}$	95	A

Freewheeling Diode			
I_F	$T_j = 175\text{ }^\circ\text{C}$	$T_s = 25\text{ }^\circ\text{C}$	31 A
		$T_s = 70\text{ }^\circ\text{C}$	24 A
I_{FRM}	$I_{FRM} = 2 \times I_{Fnom}$	40	A
I_{FSM}	$t_p = 10\text{ ms}$; half sine wave $T_j = 150\text{ }^\circ\text{C}$	95	A

Module			
$I_{t(RMS)}$			A
T_{vj}		-40 ... +175	$^\circ\text{C}$
T_{stg}		-40 ... +125	$^\circ\text{C}$
V_{isol}	AC, 1 min.	2500	V

Characteristics		$T_s = 25\text{ }^\circ\text{C}$, unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
IGBT					
$V_{GE(th)}$	$V_{GE} = V_{CE}$, $I_C = 0,29\text{ mA}$	5	5,8	6,5	V
I_{CES}	$V_{GE} = 0\text{ V}$, $V_{CE} = V_{CES}$ $T_j = 25\text{ }^\circ\text{C}$			0,0011	mA
I_{GES}	$V_{CE} = 0\text{ V}$, $V_{GE} = 20\text{ V}$ $T_j = 25\text{ }^\circ\text{C}$			300	nA
V_{CE0}		$T_j = 25\text{ }^\circ\text{C}$	0,9	1,1	V
		$T_j = 150\text{ }^\circ\text{C}$	0,8	1	V
r_{CE}	$V_{GE} = 15\text{ V}$	$T_j = 25\text{ }^\circ\text{C}$	27,5	37,5	$\text{m}\Omega$
		$T_j = 150\text{ }^\circ\text{C}$	40	52,5	$\text{m}\Omega$
$V_{CE(sat)}$	$I_{Cnom} = 20\text{ A}$, $V_{GE} = 15\text{ V}$	$T_j = 25\text{ }^\circ\text{C}_{chiplev.}$	1,45	1,85	V
		$T_j = 150\text{ }^\circ\text{C}_{chiplev.}$	1,65	2,05	V
C_{ies}	$V_{CE} = 25$, $V_{GE} = 0\text{ V}$ $f = 1\text{ MHz}$		1,1		nF
C_{oes}			0,071		nF
C_{res}			0,032		nF
$t_{d(on)}$	$R_{Gon} = 33\text{ }\Omega$	$V_{CC} = 300\text{ V}$ $I_C = 20\text{ A}$	21		ns
t_r			19		ns
E_{on}	$R_{Goff} = 33\text{ }\Omega$	$T_j = 150\text{ }^\circ\text{C}$ $V_{GE} = -7/+15\text{ V}$	0,4		mJ
$t_{d(off)}$			230		ns
t_f			50		ns
E_{off}			1,07		mJ
$R_{th(j-s)}$	per IGBT		1,95		K/W



SEMITOP[®] 3

IGBT Module

SK20MLI066

Target Data

Features


- Compact design
- One screw mounting
- Heat transfer and isolation through direct copper bonded aluminium oxide ceramic (DCB)
- Trench IGBT technology
- CAL technology FWD

Typical Applications*

- 3 Level Inverter
- UPS

Remarks

- Visol = 3000V AC, 1s, 50Hz
- Dynamic measure: DUT= IGBT (Gate pin 1) and Neutral Clamp Diode (Kathode pin 16) as free-wheeling diode











MLI


Characteristics					
Symbol	Conditions	min.	typ.	max.	Units
Inverse Diode (Antiparallel Diode)					
$V_F = V_{EC}$	$I_{Fnom} = 20 \text{ A}; V_{GE} = 0 \text{ V}$	$T_j = 25 \text{ }^\circ\text{C}_{chiplev.}$	1,6	1,9	V
		$T_j = 150 \text{ }^\circ\text{C}_{chiplev.}$	1,65	1,95	V
V_{F0}		$T_j = 25 \text{ }^\circ\text{C}$	1	1,1	V
		$T_j = 150 \text{ }^\circ\text{C}$	0,9	1	V
r_F		$T_j = 25 \text{ }^\circ\text{C}$	30	40	mΩ
		$T_j = 150 \text{ }^\circ\text{C}$	37,5	47,5	mΩ
I_{RRM}	$I_F = 20 \text{ A}$	$T_j = 150 \text{ }^\circ\text{C}$			A
Q_{rr}	$di/dt = -2000 \text{ A}/\mu\text{s}$				μC
E_{rr}	$V_R = 300 \text{ V}$		0,2		mJ
$R_{th(j-s)D}$	per diode		2,46		K/W
Freewheeling Diode (Neutral Clamp diode)					
$V_F = V_{EC}$	$I_{Fnom} = 20 \text{ A}; V_{GE} = 0 \text{ V}$	$T_j = 25 \text{ }^\circ\text{C}_{chiplev.}$	1,5		V
		$T_j = 150 \text{ }^\circ\text{C}_{chiplev.}$	1,5		V
V_{F0}		$T_j = 25 \text{ }^\circ\text{C}$	1		V
		$T_j = 150 \text{ }^\circ\text{C}$	0,9		V
r_F		$T_j = 25 \text{ }^\circ\text{C}$	20		V
		$T_j = 150 \text{ }^\circ\text{C}$	25		V
I_{RRM}	$I_F = 20 \text{ A}$	$T_j = 150 \text{ }^\circ\text{C}$	20		A
Q_{rr}	$di/dt = -2000 \text{ A}/\mu\text{s}$		1		μC
E_{rr}	$V_R = 300 \text{ V}$		0,2		mJ
$R_{th(j-s)FD}$	per diode		2,46		K/W
M_s	to heat sink		2,25	2,5	Nm
w			30		g

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.


* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.







Case T 76 (Suggested hole diameter, in the PCB, for solder pins and plastic mounting pins: 2mm)



Case T 76

MLI