

SKiiP 36NAB126V1



MiniSKiiP® 3

3-phase bridge rectifier +
brake chopper + 3-phase
bridge inverter
SKiiP 36NAB126V1

Features


- Fast Trench IGBTs
- Robust and soft freewheeling diodes in C&AL technology
- Highly reliable spring contacts for electrical connections
- UL recognised file no. E63532

Typical Applications*

- Inverter up to 36 kVA
- Typical motor power 18,5 kW

Remarks

- V_{CEsat} , V_F = chip level value



NAB

Absolute Maximum Ratings		$T_B = 25^\circ\text{C}$, unless otherwise specified	
Symbol	Conditions	Values	Units
IGBT - Inverter, Chopper			
V_{CES}		1200	V
I_C	$T_B = 25 (70)^\circ\text{C}$	88 (66)	A
I_{CRM}		140	A
V_{GES}		± 20	V
T_J		-40 ... +150	$^\circ\text{C}$
Diode - Inverter, Chopper			
I_F	$T_B = 25 (70)^\circ\text{C}$	91 (68)	A
I_{FRM}		140	A
T_J		-40 ... +150	$^\circ\text{C}$
Diode - Rectifier			
V_{RRM}		1600	V
I_F	$T_B = 70^\circ\text{C}$	61	A
I_{FSM}	$t_p = 10 \text{ ms, sin } 180^\circ, T_J = 25^\circ\text{C}$	700	A
i^2t	$t_p = 10 \text{ ms, sin } 180^\circ, T_J = 25^\circ\text{C}$	2400	A^2s
T_J		-40 ... +150	$^\circ\text{C}$
Module			
I_{RMS}	per power terminal (20 A / spring)	80	A
T_{stg}		-40 ... +125	$^\circ\text{C}$
V_{Isol}	AC, 1 min.	2500	V

Characteristics		$T_B = 25^\circ\text{C}$, unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
IGBT - Inverter, Chopper					
V_{CEsat}	$I_{Cnom} = 70 \text{ A}, T_J = 25 (125)^\circ\text{C}$		1,7 (2)	2,1 (2,4)	V
$V_{GE(TH)}$	$V_{GE} = V_{CE}, I_C = 3 \text{ mA}$	5	5,8	6,5	V
$V_{GE(TO)}$	$T_J = 25 (125)^\circ\text{C}$		1 (0,9)	1,2 (1,1)	V
r_T	$T_J = 25 (125)^\circ\text{C}$		10 (16)	13 (19)	m Ω
C_{iss}	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$		4,8		nF
C_{oss}	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$		1		nF
C_{res}	$V_{CE} = 25 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$		0,6		nF
$R_{\theta(j-s)}$	per IGBT		0,5		K/W
$t_{i(on)}$	under following conditions		80		ns
t_r	$V_{CC} = 600 \text{ V}, V_{GE} = \pm 15 \text{ V}$		25		ns
$t_{i(off)}$	$I_{Cnom} = 70 \text{ A}, T_J = 125^\circ\text{C}$		390		ns
t_f	$R_{Con} = R_{Coff} = 9 \Omega$		90		ns
E_{on}	inductive load		9		mJ
E_{off}			7,7		mJ
Diode - Inverter, Chopper					
$V_F = V_{EC}$	$I_{Fnom} = 70 \text{ A}, T_J = 25 (125)^\circ\text{C}$		1,5 (1,5)	1,7 (1,7)	V
$V_{(TO)}$	$T_J = 25 (125)^\circ\text{C}$		1 (0,8)	1,1 (0,9)	V
r_T	$T_J = 25 (125)^\circ\text{C}$		7,1 (10)	8,6 (11)	m Ω
$R_{\theta(j-s)}$	per diode		0,7		K/W
I_{FRM}	under following conditions		77		A
C_{rr}	$I_{Fnom} = 70 \text{ A}, V_{RR} = 600 \text{ V}$		18		μC
E_{rr}	$V_{GE} = 0 \text{ V}, T_J = 125^\circ\text{C}$		7,5		mJ
	$di_F/dt = 2000 \text{ A}/\mu\text{s}$				
Diode - Rectifier					
V_F	$I_{Fnom} = 35 \text{ A}, T_J = 25^\circ\text{C}$		1,1		V
$V_{(TO)}$	$T_J = 150^\circ\text{C}$		0,8		V
r_T	$T_J = 150^\circ\text{C}$		11		m Ω
$R_{\theta(j-s)}$	per diode		0,9		K/W
Temperature Sensor					
R_{ts}	$\pm 3\%, T_r = 25 (100)^\circ\text{C}$		1000(1670)		Ω
Mechanical Data					
w			95		g
M_b	Mounting torque		2	2,5	Nm




Fig. 1 Typ. output characteristic




Fig. 2 Typ. rated current vs. temperature




Fig. 3 Typ. transfer characteristic




Fig. 4 Reverse bias safe operating area




Fig. 5 Typ. Turn-on / off energy = $f(I_C)$










Fig. 6 Typ. Turn-on / off energy = $f(R_G)$





This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX.

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.